

RDC-5K



Specification:
 Number of Keys: 113
 Key switch Technology: Short travel keys
 Actuation Force/Travel: 2.0 N / 1.3mm
 Key switch Lifetime: 10 Million
 Protection Level: IP65, NEMA 4x
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 406.4 x 44.5mm
 19" x 15" x 1.75" (19"; 1U)
 Weight: 3680g
 Operating Temperature: -40 °C to 60 °C

Item No.	Product Name
RDC-5K-PS2	RDC-5K with PS/2 cable
RDC-5K-USB	RDC-5K with USB cable
RDC-5K-16-T-xxx	RDC-5K with 16" Rails T-Handle
RDC-5K-17-RX-xxx	RDC-5K with 16" Rails T-Handle with Key

RDC-1000

Specification:
 Number of Keys: 114
 Key switch Technology: Short travel keys
 Actuation Force/Travel: 2.0 N / 1.3mm
 Key switch Lifetime: 10 Million
 Protection Level: IP65, NEMA 4x
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 406.4 x 44.5mm
 19" x 15" x 1.75" (19"; 1U)
 Weight: 6900g
 Operating Temperature: -40 °C to 60 °C



Item No.	Product Name
RDC-1000-PS2	RDC-1000 with PS/2 cable
RDC-1000-USB	RDC-1000 with USB cable
RDC-1000-16-T-xxx	RDC-1000 with 16" Rails T-Handle
RDC-1000-16-RX-xxx	RDC-1000 with 16" Rails T-Handle with Key

RDC-1535



Specification:
 Number of Keys: 101
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.5 N / 3.0mm
 Key switch Lifetime: 10 Million
 Protection Level: IP65/IP20 (draw closed/open)
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 406.4 x 44.5mm
 19" x 15" x 1.75" (19"; 1U)
 Weight: 7360g
 Operating Temperature: -40 °C to 60 °C

Item No.	Product Name
RDC-1535-PS2	RDC-1535 with PS/2 cable
RDC-1535-USB	RDC-1535 with USB cable
RDC-1535-16-T-xxx	RDC-1535 with 16" Rails T-Handle
RDC-1535-16-RX-xxx	RDC-1535 with 16" Rails T-Handle with Key

RDC-3000



Specification:
 Number of Keys: 113
 Key switch Technology: Short travel keys
 Actuation Force/Travel: 2.0 N / 1.3mm
 Key switch Lifetime: 10 Million
 Protection Level: IP65, NEMA 4x
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 406.4 x 44.5mm
 19" x 15" x 1.75" (19"; 1U)
 Weight: 7360g
 Operating Temperature: -40 °C to 60 °C

Item No.	Product Name
RDC-3000-PS2	RDC-3000 with PS/2 cable
RDC-3000-USB	RDC-3000 with USB cable
RDC-3000-16-T-xxx	RDC-3000 with 16" Rails T-Handle
RDC-3000-17-RX-xxx	RDC-3000 with 16" Rails T-Handle with Key

ACK-730

Specification:
 Number of Keys: 104
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.6 N / 4.0mm
 Key switch Lifetime: 10 Million
 Protection Level: IP65/IP20 (draw closed/open)
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 326.2 x 44.4mm
 19" x 13" x 1.75" (19"; 1U)
 Weight: 6800g
 Operating Temperature: 0 °C to 55 °C



Item No.	Product Name
ACK-730-PB-MRP	ACK-730 with PS/2 cable
ACK-730-UB-MRP	ACK-730 with USB cable

TKL-107-TOUCH-SCHUBL-WHITE



Specification:
 Number of Keys: 107
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.5 N / 3.0mm
 Key switch Lifetime: 6 Million
 Protection Level: IP20
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 350.5 x 44.5mm
 19" x 13.8" x 1.75" (19"; 1U)
 Weight: 6000g
 Operating Temperature: -40 °C to 60 °C

Item No.	Product Name
KL00221	TKL-107-TOUCH-SCHUBL-WHITE-PS/2-US

TKL-84a-4400-SCHUBL



Specification:
 Number of Keys: 84
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.5 N / 3.0mm
 Key switch Lifetime: 20 Million
 Protection Level: IP65/IP20 (draw closed/open)
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 220 x 44.5mm
 19" x 8.6" x 1.75" (19"; 1U)
 Weight: 6000g
 Operating Temperature: -40 °C to 60 °C

Item No.	Product Name
KL01227	TKL-84a-4400-SCHUBL-PS/2-US
KL02026	TKL-84a-4400-SCHUBL-USB-US

TKL-102-IP65-SCHUBL

Specification:
 Number of Keys: 104
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.6 N / 4.0mm
 Key switch Lifetime: 5 Million
 Protection Level: IP65/IP20 (draw closed/open)
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 326.2 x 44.4mm
 19" x 13" x 1.75" (19"; 1U)
 Weight: 6500g
 Operating Temperature: -40 °C to 60 °C



Item No.	Product Name
KL09246	TKL-102-IP65-SCHUBL-PS/2-US

RAC-116



Specification:
 Number of Keys: 105
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.5 N / 3.0mm
 Key switch Lifetime: 10 Million
 Protection Level: IP20
 Mounting Type: 19" rack mount
 Dimensions: 400 x 238 x 34mm
 Weight: 7000g
 Operating Temperature: 0 °C to 55 °C

Item No.	Product Name
RAC-116W	Rack-mount Keyboard & Touchpad Drawer, beige
RAC-116B	Rack-mount Keyboard & Touchpad Drawer, black

15" LCD Keyboard Drawer Unicorn 15



Specification:
 Number of Keys: 106
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.6 N / 3.0mm
 Key switch Lifetime: 1 Million
 Protection Level: IP20
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 527 x 44.5mm
 19" x 20.7" x 1.75" (19"; 1U)
 Weight: 16kg
 Operating Temperature: 0 °C to 50 °C

Item No.	Product Name
Unicorn 15	15" LCD Keyboard Drawer

17" LCD Keyboard Drawer Unicorn 17

Specification:
 Number of Keys: 106
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.6 N / 3.0mm
 Key switch Lifetime: 1 Million
 Protection Level: IP20
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 532 x 44.5mm
 19" x 20.9" x 1.75" (19"; 1U)
 Weight: 17.5kg
 Operating Temperature: 0 °C to 50 °C



Item No.	Product Name
Unicorn 17	17" LCD Keyboard Drawer

KD 8170N – 17" LCD



Specification:
 Number of Keys: 104
 Key switch Technology: Long travel keys
 Actuation Force/Travel: 0.5 N / 3.0mm
 Key switch Lifetime: 5 Million
 Protection Level: IP20
 Mounting Type: 19" rack mount
 Dimensions: 482.6 x 599.4 x 44.5mm
 19" x 23.6" x 1.75" (19"; 1U)
 Weight: 18kg
 Operating Temperature: 0 °C to 50 °C

Item No.	Product Name
KD8170N	1U, 17" 1280x1024 LCD monitor Drawer, keyboard, touch pad, Black color